

RFID based Time Attendance & Access Control Terminal RFEntry2



















Stand Alone Access Control Terminal SEM01



The unit is single door multifunction standalone access controller or a Wiegand output keypad or a card reader. It is suitable for mounting indoor in harsh environments. It is housed in a strong case, which is available in Black finish. The inbuilt card reader supports 125KHZ EM cards. The unit has many extra features including lock output current short circuit protection & Wiegand output. These features makes the unit an ideal choice for door access not only for small shops and domestic households but also for commercial and industrial applications such as factories, warehouses, laboratories, banks and prisons.



RFID Card





Access Control

lp65

AT A GLANCE

| Card Capacity | 20000 |
|--------------------------|---|
| Records Capacity | 200000 |
| Card Reader inside | EM Card |
| Identification Speed | 1s |
| Identification Mode | 1:N & 1:1 |
| Identification Mode | Card / Password |
| Real Time Clock | Yes |
| Buzzer | Yes |
| LED | 2.4 Inch TFT Color LCD |
| Real Time Control | Yes |
| Access Control interface | Connect with Electronic lock, Access controller |
| Voice | High - Decimation Voice |
| Environment | Inside |
| Keyboard | 4 * 4 Button Keypads |
| Function Key | Yes |
| | |